

2/12/15

10/539930

PCT/EP03/13711  
2002P20039WOUS

- 1 -

JCO9 Rec'd PCT/PTO 17 JUN 2005

Turbine, fixing device for guide blades and working method for removing the guide blades of a turbine

The present invention relates to a turbine according to the preamble of claim 1, a fixing device for guide blades of a turbine according to the preamble of claim 9 and a method for removing the guide blades of a turbine according to the preamble of claim 11.

DE 195 46 722 A1 discloses a guide-blade carrier for a gas turbine. On its inside facing the hot-gas duct, the guide-blade carrier has a plurality of slots which are arranged one behind the other in its axial longitudinal extent and which run in an annular manner in the circumferential direction and are at the same time provided with a respective undercut. The slots serve to accommodate guide-blade roots of a guide blade. To this end, the root of a guide blade is pushed in the circumferential direction into the slot running in an annular manner.

For repair, inspection and/or maintenance work on the guide blades, they must be removed from the gas turbine. To this end, the gas turbine is opened, so that the guide-blade carrier is accessible and the guide blades can be pushed out of the slot. The opening of the gas turbine is time-consuming and requires a corresponding long shutdown of the gas turbine.

The object of the present invention is to reduce the downtimes of the turbine during repair, inspection and/or maintenance work.

The object is achieved by the features and measures of claim 1. Further advantageous configurations of the invention are given in the subclaims.

The solution according to the invention provides for the guide-blade root and/or the guide-blade tip to be capable of being

secured by means of a manually releasable clamping device. The downtimes of the gas turbine can be beneficially reduced by virtue of the fact that the guide blade to be exchanged can be removed through the accessible combustion chamber. To this end, at least one clamping device securing the guide blade can be reached from the combustion chamber. The one clamping device securing the guide-blade root is provided on the inner casing and/or the other clamping device secures the guide-blade tip and is arranged on the fixing ring. After the release of the clamping device(s), therefore, each guide blade can thus be removed from the combustion chamber without the inner casing of the turbine having to be opened.

In an advantageous development, provision is made for the clamping device to be capable of being secured to the inner casing or to the fixing housing, respectively, and for it to fasten the guide-blade root or the guide-blade tip, respectively, in an operating position by means of a tie rod running in the axial direction. During the fixing of the guide blade, the inner casing or the fixing ring, respectively, serves as an abutment for the clamping device. The tie rod fastens the clamping device first on the inner casing or on the fixing ring, respectively, and then on the guide blade.

In a further configuration, to remove the guide blade through the combustion chamber, at least that part of the clamping device which faces the combustion chamber can be removed from the clearance profile of the guide blade after the release of the tie rod. The clearance profile of the guide blade is described by the contour of the guide blade as viewed from the combustion chamber in the axial direction. The guide blade is exposed after removal of the clamping device from the clearance profile.

If, in a further configuration, the clamping device is fixed in a parking position exposing the guide-blade root or guide-blade

tip, respectively, this cannot impair the removal of the guide blades. Consequently, the clamping device cannot get caught inadvertently on the guide blade during its removal. Furthermore, the clamping device is effectively protected  
5 against falling out unintentionally. Components which have fallen out unintentionally may lead to mechanical destruction during operation of the gas turbine.

In an advantageous proposal, the clamping device comprises two  
10 radially extending retaining stops which can be fastened by means of the tie rod. The two retaining stops of a clamping device in each case enclose elements of the inner casing as abutment and at the same time the guide-blade root or the guide-blade tip, respectively. To secure the guide blade to the  
15 inner casing, the retaining stops can be fastened by means of the tie rod.

The guide blade is advantageously located in the first guide-blade row as viewed in the direction of flow of a working  
20 medium. This makes it easier to reach the guide blade from the combustion chamber.

The clamping device can expediently be removed from the inner casing after removal of the guide blade.

25 It is considered to be especially advantageous if a guide ring arranged downstream in the direction of flow of a working medium is manually accessible after removal of the clamping device fixed to the inner casing. Therefore, in a similar  
30 manner to the guide blade, the guide ring, which is subject to wear, can be reached especially easily and quickly for maintenance and/or repair work without having to open the inner casing of the turbine.

35 A fixing device for guide blades of a turbine is described by the features of claim 9.

The solution according to the invention provides for the fixing device to comprise a manually releasable clamping device accessible from the combustion chamber. The downtimes of a gas turbine can be beneficially reduced by virtue of the fact that the guide blade to be exchanged can be removed through the accessible combustion chamber. To this end, at least one clamping device, as fixing device, securing the guide blade can be reached from the combustion chamber. The one clamping device securing the guide-blade root is provided on the inner casing and/or the other clamping device secures the guide-blade tip and is arranged on the fixing ring. After the release of the clamping device(s), therefore, each guide blade can be removed from the combustion chamber without the inner casing of the turbine having to be opened.

In an advantageous configuration of the fixing device, the clamping device comprises two radially extending retaining stops which can be fastened by means of the tie rod. The two retaining stops of a clamping device in each case enclose elements of the inner casing as abutment and at the same time the guide-blade root or the guide-blade tip, respectively. To secure the guide blade to the inner casing, the retaining stops can be fastened by means of the tie rod.

A working method for removing the guide blades of a turbine is described by the features of claim 11.

The invention provides for a guide blade of the first guide-blade row as viewed in the direction of flow of the working medium to be removed manually through the combustion chamber by the sequence of the following steps:

The clamping device arranged on the inner casing is released, displaced into a parking position exposing the guide-blade root and fixed there again. If appropriate, the other clamping

device arranged at the inner fixing ring is released, so that the guide-blade tip is exposed. After that the guide blade is displaced axially against the direction of flow of the working medium, is moved radially inward if need be and is tilted about the guide-blade tip, so that the guide blade is then free after being moved radially outward. This procedure avoids opening the entire turbine and considerably reduces the downtimes of the turbine which are caused by maintenance and repair times. The parking in a parking position prevents the clamping device from accidentally falling out and thus permits the trouble-free removal of the guide blade.

The invention is explained in more detail with reference to a drawing, in which:

fig. 1 shows a gas turbine in a longitudinal partial section, and  
fig. 2 shows the combustion chamber, the hot-gas duct, the guide blade and the moving blade of the first turbine stage in a partial cross section according to fig. 1.

Figure 1 shows a gas turbine 1 in a longitudinal partial section. In the interior, the gas turbine 1 has a rotor 3 which is rotatably mounted about a rotation axis 2 and is also designated as turbine wheel. Following one another along the rotor 3 are an intake casing 4, a compressor 5, a toroidal annular combustion chamber 6 having a plurality of coaxially arranged burners 7, a turbine 8 and the exhaust-gas casing 9. In this case, the annular combustion chamber 6 forms a combustion space 17 which communicates with an annular hot-gas duct 18. The turbine 8 is formed there by four turbine stages 10 arranged one behind the other. Each turbine stage 10 is formed from two blade rings. As viewed in the direction of flow of a working medium 11, a row 14 formed from

moving blades 15 follows a guide-blade row 13 in the hot-gas duct 18. In this case, the guide blades 12 are fixed to the stator 23, whereas the moving blades 15 of a row 14 are attached to the rotor 3 by means of a turbine disk 19. A  
5 generator or a driven machine (not shown) is coupled to the rotor 3.

During the operation of the gas turbine 1, air 16 is drawn in through the intake casing 4 and compressed by the compressor 5.  
10 The compressed air provided at the turbine-side end of the compressor 5 is passed to the burners 7 and is mixed there with a fuel. The mixture is then burned in the combustion space 17 while forming the working medium 11. From there, the working medium 11 flows along the hot-gas duct 18 past the guide blades  
15 12 and the moving blades 15. The working medium 11 expands at the moving blades 15 in an impulse-transmitting manner, so that the moving blades 15 drive the rotor 3 and the latter drives the driven machine coupled to it.

20 The components exposed to the hot working medium 11 are subjected to thermal loads during the operation of the gas turbine 1. The guide blades 12 and moving blades 15 of the first turbine stage 10 as viewed in the direction of flow of the working medium 11, in addition to the heat shield blocks  
25 lining the annular combustion chamber 6, are subjected to the greatest thermal loading. In order to withstand the temperatures prevailing there, said guide blades 12 and moving blades 15 are cooled by means of a coolant.

30 Fig. 2 shows a section through a partly shown annular combustion chamber 6 and through the first turbine stage 10, which is formed from the guide blade 12 and the downstream moving blade 15. In this case, the blades 12, 15 are arranged radially around the rotor 3 of the gas turbine. The moving  
35 blade 15 sits on a turbine disk 19, which is arranged on the rotor 3, whereas the guide blade 12 is

fixed to the stator. The guide blade 12 has a guide-blade root 21 facing the inner casing 20 of the turbine 8 and a guide-blade tip 22 opposite the guide-blade root 21. The guide-blade tip 22 faces the rotor 3 and is secured to a fixing ring 24 of  
5 the stator 23.

A clamping device 25 arranged at the guide-blade root 21 and at the inner casing 20 is located in an operating position. The clamping device 25 comprises two retaining stops 26, 27 and a  
10 helical tie rod 28, which is only intimated here. The retaining stop 27 encloses a projection 29 which is integrally formed on the guide-blade root 21 and extends parallel to the axial direction of the rotor 3. A further projection 30 extending in the radial direction of the rotor 3 is likewise integrally  
15 formed on the guide-blade root 21. This projection 30 projects in between the two retaining stops 26, 27 in such a way that the latter firmly clamp the projection 30 in place when the tie rod 28 is fastened. The inner casing 20 serves as an abutment for the clamping device 25, which secures the guide-blade root  
20 21 and thus also the guide blade 12 itself.

The tie rod 28 runs through the inner casing 20, in which case it extends through an axial bore 32 which is in the shape of an elongated hole as viewed in the radial direction. Arranged next  
25 to it radially on the outside on the inner casing 20 is a projection 31.

In a similar manner to the arrangement at the guide-blade root 21, a further clamping device 25 is arranged in its operating  
30 position at the guide-blade tip 22 and at the fixing ring 24. This clamping device 25 has two retaining stops 36, 37 which clamp a radially protruding third projection 33 in place on the fixing ring 24 by means of a tie rod 38, this projection 33 being integrally formed on the guide-blade tip 22.

To remove the guide blade 12, the following steps are carried out after the clamping devices 25, 35 in the combustion chamber, which can be reached by a fitter, have been exposed:

5 The clamping device 25 arranged at the guide-blade root 21 is released by the two retaining stops 26, 27 being slackened by the release of the tie rod 28 to such an extent that the retaining stop 27 releases the projection 29. At the same time, the retaining stop 26 is displaced in the direction of the  
10 annular combustion chamber 6 to such an extent that the projection 31 can be enclosed by said retaining stop 26. The clamping device 25, i.e. the first retaining stop 26, the second retaining stop 27 and the tie rod 28, is then moved radially outward as a unit. To this end, the axial bore 32 is  
15 designed like an elongated hole in cross section. The tie rod 28 is fastened again in the radially outer position, so that the clamping device 25 is located in its parking position in a secured manner. The guide-blade root 21 is completely released from it. As viewed from the annular combustion chamber 6, the  
20 contour of the first retaining stop 26 is located outside the contour of the guide-blade root 21, i.e. the clamping device 25 is located outside the clearance profile of the guide blade 12.

The guide-blade tip 22 is exposed in a similar manner by the  
25 tie rod 38 of the clamping device 35 arranged on the fixing ring 24 being released for this purpose, so that the retaining stops 36, 37 release a third projection 33 integrally formed on the guide-blade tip 22. The movable clamping device 35 is moved radially inward to such an extent that it encloses a projection  
30 34 of the fixing ring 24. The clamping device 35 is then fastened again, so that it is located in its parking position. In a similar manner to the clamping device 25 at the guide-blade root 21, the clamping device 35 arranged at the guide-blade tip 22 is located outside the clearance profile of the  
35 guide blade 12.



The guide blade 12 thus exposed can now be removed from the guide-blade row 13 by being displaced against the direction of flow of the working medium 11 and by then being displaced slightly radially inward. This displacement path is identified  
5 by the arrow 40. The guide blade 12 is then tilted about the guide-blade tip 22 in the direction of the combustion chamber 6. After that, the guide blade 12 is moved into the combustion space 17 of the annular combustion chamber 6 and removed from the gas turbine 1.